



**Faculty of Engineering**

**POST-FLOOD FORENSIC ANALYSIS ON SMALL URBAN  
CATCHMENT USING ONE DIMENSIONAL SYSTEM MODELING**

**Ting Sie Chun**

**Master of Engineering  
2011**

**Pusat Khidmat Maklumat Akademik  
UNIVERSITI MALAYSIA SARAWAK**  
**POST-FLOOD FORENSIC ANALYSIS ON SMALL URBAN CATCHMENT  
USING ONE DIMENSIONAL SYSTEM MODELING**

**P.KHIDMAT MAKLUMAT AKADEMIK**

**UNIMAS**



**1000246340**

**TING SIE CHUN**

A thesis submitted  
in fulfilment of the requirement for the degree of  
Master of Engineering  
(Water Resource Engineering)

Faculty of Engineering  
UNIVERSITI MALAYSIA SARAWAK  
2011

# UNIVERSITI MALAYSIA SARAWAK

## BORANG PENGESAHAN STATUS TESIS

Judul:

**POST-FLOOD FORENSIC ANALYSIS ON SMALL URBAN  
CATCHMENT USING ONE DIMENSIONAL SYSTEM MODELING**

**SESI PENGAJIAN: 2011**

Saya

**TING SIE CHUN**  
**(HURUF BESAR)**

mengaku membenarkan tesis \* ini disimpan di Pusat Khidmat Maklumat Akademik, Universiti Malaysia Sarawak dengan syarat-syarat kegunaan seperti berikut:

1. Tesis adalah hakmilik Universiti Malaysia Sarawak.
2. Pusat Khidmat Maklumat Akademik, Universiti Malaysia Sarawak dibenarkan membuat salinan untuk tujuan pengajian sahaja.
3. Membuat pendigitan untuk membangunkan Pangkalan Data Kandungan Tempatan.
4. Pusat Khidmat Maklumat Akademik, Universiti Malaysia Sarawak dibenarkan membuat salinan tesis ini sebagai bahan pertukaran antara institusi pengajian tinggi.
5. \*\* Sila tandakan ( ✓ ) di kotak yang berkenaan

☐

SULIT

(Mengandungi maklumat yang berdarjah keselamatan atau kepentingan Malaysia seperti yang termaktub di dalam AKTA RAHSIA RASMI 1972).


☐

TERHAD


(Mengandungi maklumat TERHAD yang telah ditentukan oleh organisasi/ badan di mana penyelidikan dijalankan).

☒

TIDAK TERHAD



(TANDATANGAN PENULIS)

Disahkan oleh  


(TANDATANGAN PENYELIA)

Alamat tetap:

No.3C, Jalan Cherry,  
96000 Sibu,  
Sarawak.

Prof. Dr. Frederik Josep Putuhena  
(Nama Penyelia)

Tarikh:

26<sup>th</sup> May 2011

Tarikh:

26 May 2011

### CATATAN

- \* Tesis dimaksudkan sebagai tesis bagi Ijazah Doktor Falsafah, Sarjana dan Sarjana Muda.
- \*\* Jika tesis ini SULIT atau TERHAD, sila lampirkan surat daripada pihak berkuasa/organisasi berkenaan dengan menyatakan sekali sebab dan tempoh tesis ini perlu dikelaskan sebagai SULIT dan TERHAD.

# UNIVERSITI MALAYSIA SARAWAK

## BORANG PENGESAHAN STATUS TESIS

Judul:

**POST-FLOOD FORENSIC ANALYSIS ON SMALL URBAN  
CATCHMENT USING ONE DIMENSIONAL SYSTEM MODELING**

**SESI PENGAJIAN: 2011**

Saya

**TING SIE CHUN**  
**(HURUF BESAR)**

mengaku membenarkan tesis \* ini disimpan di Pusat Khidmat Maklumat Akademik, Universiti Malaysia Sarawak dengan syarat-syarat kegunaan seperti berikut:

1. Tesis adalah hakmilik Universiti Malaysia Sarawak.
2. Pusat Khidmat Maklumat Akademik, Universiti Malaysia Sarawak dibenarkan membuat salinan untuk tujuan pengajian sahaja.
3. Membuat pendigitan untuk membangunkan Pangkalan Data Kandungan Tempatan.
4. Pusat Khidmat Maklumat Akademik, Universiti Malaysia Sarawak dibenarkan membuat salinan tesis ini sebagai bahan pertukaran antara institusi pengajian tinggi.
5. \*\* Sila tandakan ( ✓ ) di kotak yang berkenaan

☐ SULIT


(Mengandungi maklumat yang berdarjah keselamatan atau kepentingan Malaysia seperti yang termaktub di dalam AKTA RAHSIA RASMI 1972).

☐ TERHAD

(Mengandungi maklumat TERHAD yang telah ditentukan oleh organisasi/badan di mana penyelidikan dijalankan).

☒ TIDAK TERHAD

  
(TANDATANGAN PENULIS)

Disahkan oleh  
  
(TANDATANGAN PENYELIA)

Alamat tetap: No.3C, Jalan Cherry,  
96000 Sibu,  
Sarawak.

Prof. Dr. Frederik Josep Putuhena  
(Nama Penyelia)

Tarikh: 26<sup>th</sup> May 2011

Tarikh:

26 May 2011

### CATATAN

- \* Tesis dimaksudkan sebagai tesis bagi Ijazah Doktor Falsafah, Sarjana dan Sarjana Muda.  
\*\* Jika tesis ini SULIT atau TERHAD, sila lampirkan surat daripada pihak berkuasa/organisasi berkenaan dengan menyatakan sekali sebab dan tempoh tesis ini perlu dikelaskan sebagai SULIT dan TERHAD.

“I declare that I have read through this project report and to my opinion  
this project report is sufficient in term of scope and quality for the purpose of  
awarding the degree of Master of Water Resources Engineering”

Signature:  .....

Name of Supervisor: **Professor Dr. Frederik Josep Putuhena**

Signature:  .....

Name of Co-supervisor: **Professor Dr. Salim Said**

Title: Post-Flood Forensic Analysis on Small Urban Catchment Using One  
Dimensional System Modeling

Date: 26<sup>th</sup> May 2011

I declare that this project report entitled “**Post-Flood Forensic Analysis on Small Urban Catchment Using One Dimensional System Modeling**” is the result of my own work except as cited in the references. The report has not been accepted for any degree and is not currently submitted in candidature of any other degree.

Signature:  .....

Name of Candidate: Ting Sie Chun

Date: 26<sup>th</sup> May 2011

*To my beloved family*  
*And all of my friends in Unimas*



# ACKNOWLEDGEMENT

In preparing this research, I was in contact with many people, academicians, researchers and engineers. They have contributed towards my understanding and thoughts. First and foremost, I would like to express my sincere gratitude to my supervisor, Professor Frederik Josep Putuhena and co-supervisor, Professor Salim Said for the unceasing attention and guidance during the entire course of this research because without their support, I would not be able to complete my thesis with excellence.

I would also like to convey my thanks to State Planning Unit of Sarawak, Sarawak Information and Communication Technology (ICT) Unit, Sarawak Land and Survey Department, Sarawak Drainage and Irrigation Department (DID), Jabatan Kerja Raya (JKR), Sibuan and Sarawak Marine Department which are willing to provide the data required for the successful completion of this research. I would like to thank Ir. Ting Sing Kwong- Sibuan Divisional Engineer and Mr. Sim Sia Po from Sibuan DID for their willingness to share their knowledge on the subject of this research.

Last but not least, my thanks also go to my beloved parents for their undivided love and support given to me throughout the completion of my research. I want to convey my love towards my parents by dedicating my success to them.



# ABSTRACT

( A 0.47 km<sup>2</sup> of residential houses in Sungai Merah (SM) in the Sibu Town of Sarawak State is located within the Seduan River basin, which is a flood-prone area with relatively flat and typically low-lying floodplain. Poor maintenance, severe conditions and water logging in the current drainage system have causes flooding with addition to water-logged soil-peat. The Wallingford Software model-InfoWorks Collection System (CS), coupled with its embedded Geographic Information System (GIS) applications, is one approach that used to identify the causes of inundation, and to improve performance of the 16 km-drainage system. )

Results show that flooding in SM area is triggered by tidal influences from the Seduan River. Some part of the drainage system in SM area failed to manoeuvre the flood water using the current existing drainage facilities. Flood mitigation in SM area is part of the Sibu Town urban water management system, which a proposed 3.7 m LSD high levee will be constructed along the Seduan River to protect the residential area from tidal impact. Tidal gates are also provided to overcome the internal drainage problems. The hydrodynamic modeling has shown its capability in identifying the effectiveness of the levee in Sungai Merah area. From this research, it is found that the levee constructed is satisfactory to prevent deluge in SM area for 20 years ARI. The simulated model is useful for the integrated assessment of flood conditions in SM area, for cost-benefit assessment and risk-based design of flood protection measures and hence, it is as a decision support tool for flood risk management.

# ABSTRAK

Kawasan perumahan dengan keluasan  $0.47 \text{ km}^2$  di Sungai Merah (SM), Bandar Sibu, Sarawak terletak di dalam lembangan Sungai Seduan merupakan kawasan yang kerap banjir dengan dataran banjir yang lazimnya rendah dan mendatar. Sistem perparitan semasa yang tiada penyelenggaraan, keadaan penyaliraaan parit yang parah serta tergenang air telah mengakibatkan banjir. Tanah yang carak seperti tanah gambut memburukkan lagi keadaan banjir di SM. Sistem Perisian Wallingford-InfoWorks Collection System (CS), digandingkan dengan aplikasi Geographic Information System (GIS) adalah satu pendekatan untuk mengenalpasti punca-punca berlakunya banjir dan mengenalpasti cara-cara meningkatkan prestasi sistem perparitan sepanjang 16 km. Keputusan simulasi menunjukkan banjir di SM dipengaruhi oleh pasang surut dari Sungai Seduan. Seseengah bahagian dalam sistem perparitan sedia ada di kawasan SM gagal untuk mengawal keadaan air banjir. Tebatan banjir dalam kawasan SM ialah salah satu bahagian sistem pengurusan air di Bandar Sibu yang mana pembinaan tetambak setinggi 3.7 m LSD sepanjang Sungai Seduan dicadangkan untuk melindungi kawasan perumahan dari kesan pasang surut. Pintu air pasang surut juga disediakan untuk mengatasi masalah saliran perparitan dalaman. Model hidrodinamik memperagakan bukti keupayaannya dalam mengenalpasti keberkesanan tetambak di kawasan SM. Dari penyelidikan ini, didapati tetambak yang dibina telah berjaya menghalang banjir di kawasan SM untuk 20 tahun ARI. Model simulasi berkenaan berguna untuk penilaian bersepadu keadaan banjir di kawasan SM untuk langkah-langkah perlindungan banjir dari segi penilaian kos dan reka bentuk berasaskan

risiko bagi langkah-langkah perlindungan banjir dan sekaligus bertindak sebagai alat sokongan untuk pengurusan risiko banjir.

# **TABLE OF CONTENTS**

	<b>Page</b>
<b>DEDICATION</b>	i
<b>ACKNOWLEDGEMENT</b>	ii
<b>ABSTRACT</b>	iii
<b>ABSTRAK</b>	iv
<b>TABLE OF CONTENTS</b>	vi
<b>LIST OF TABLES</b>	x
<b>LIST OF FIGURES</b>	xi
 <b>CHAPTER 1: INTRODUCTION</b>	
1.1 Introduction	1
1.2 Background Information	4
1.3 Problem Definition	17
1.4 Aim and Objectives	18
1.5 Scope of Study	19
1.6 Limitations of the Study	19
1.7 Thesis Structure	20
 <b>CHAPTER 2: LITERATURE REVIEW</b>	
2.1 Introduction	22
2.2 Review of Flood Disasters in Sibu Town	23



3.6 Model Sensitivity Test	72
----------------------------	----

## **CHAPTER 4: RESULTS, ANALYSIS AND DISCUSSION**

4.1 Introduction	76
4.2 Model Performance and Calibration	77
4.2.1 Manning's Roughness Coefficient	77
4.2.2 Curve Number (CN)	84
4.3 Analysis of Existing Drainage System	96
4.4 Flood Risk Management Plan	105
4.4.1 Effects of the Levee on Sungai Merah Residential Area	106
4.4.2 Performances of the Levee	112

## **CHAPTER 5: CONCLUSIONS AND RECOMMENDATIONS**

5.1 Introduction	118
5.2 Conclusions	119
5.3 Recommendations for Future Research	120

<b>REFERENCES</b>	122
-------------------	-----

## **APPENDICES**

Appendix A: Details of Topographical Map
Appendix B: Details of Seduan River Basin Map
Appendix C: Manning Formula

Appendix D: Soil Conservation Service (SCS) Hydrographs

Appendix E: Soil Conservation Service (SCS) Curve

Number

Appendix F: Newspaper Cutting on Drainage System in

Sibu Town

Appendix G: Locality Plan of the Project Site

Appendix H: Tidal Gate Control



## LIST OF TABLES

Tables	Page
Table 1.1      Historical flood events recorded in Sibul Town, 1997-2009	13
Table 4.1      Model calibrations for Point 1	78
Table 4.2      Model calibrations for Point 2	80
Table 4.3      Model calibrations for Point 3	82
Table 4.4      Calculated SCS Runoff Hydrograph on 26 December 2008	85
Table 4.5      Modeled Runoff Hydrograph on 26 December 2008	86
Table 4.6      Calculated SCS Runoff Hydrograph on 26 February 2009	87
Table 4.7      Modeled Runoff Hydrograph on 26 February 2009	88
Table 4.8      Results of model calibration and verification for Curve Number	88
Table 4.9      Observed and modeled water level on December 26, 2008	90
Table 4.10     Comparison of flow, velocity and average flood depth with internal and external flood	101
Table 4.11     Maximum flow and water depth under different ARI events	114

## LIST OF FIGURES

Figures	Page
Figure 1.1 Existing of sandbar at the mouth of Seduan River	3
Figure 1.2 Rajang River consists of many tributaries	4
Figure 1.3 Rainfall stations and river gauging stations in upper Rajang River	5
Figure 1.4 Rainfall stations and river gauge stations in lower Rajang River	6
Figure 1.5 Layout plan of Sibu Town	7
Figure 1.6 Topography of Sibu Town	8
Figure 1.7 Relationship between drainage and ground subsidence	10
Figure 1.8 More development rose along Seduan River	11
Figure 1.9 SM during 1963 flood	12
Figure 1.10 Location of the study area	15
Figure 1.11 Topographical map of SM with drainage flow direction from the inlet to the outlet	16
Figure 2.1 Inundation of Sibu Town February 2001	24
Figure 2.2 Catholic Church located at Upper Lanang in Sibu was flooded in January 2004	25
/ Figure 2.3 Inundation of Sibu Town December 2007	25
Figure 2.4 Upper Lanang Road during July 2008 flood	26
Figure 2.5 Inundation of Upper Lanang Jun 2009	26

Figure 2.6	On-going construction of pump station at Rajang River	30
Figure 2.7	Improvement of drainage system in Ulu SM, Sibul	31
Figure 2.8	Current situations that causes flood to Sibul Town	33
Figure 2.9	Control volume for derivation of unsteady continuity equation	40
Figure 2.10	Control volume for derivation of unsteady momentum equation	43
Figure 2.11	Internal boundary conditions	51
Figure 3.1	Flowchart of research methodology	55
Figure 3.2	Flowchart on calibration and verification methodology	56
Figure 3.3	Water level versus rainfall depth on May 2, 2010	57
Figure 3.4	Water level versus rainfall depth on February 26, 2009	58
Figure 3.5	Water level versus rainfall depth on December 26, 2008	58
Figure 3.6	SM drainage basin	61
Figure 3.7	Proposed 3.7m levee along Seduan River	62
Figure 3.8	Proposed flap gate at the outlet	62
Figure 3.9	Geo-referencing Seduan River using ArcMap	64
Figure 3.10	Aerial view featuring SM residential area	65
Figure 3.11	TIN model featuring SM catchment ground level	67
Figure 3.12	TIN surface model of SM's houses, drainage, roads, land-use, river and utilizes	67

Figure 3.13	DTM of SM residential area without levee	68
Figure 3.14	DTM of SM residential area with levee	68
Figure 3.15	Model of SM drainage system	70
Figure 3.16	Calibration locations in SM residential area	73
Figure 4.1	Calibration result for SM area during May 2, 2010 for Point 1	79
Figure 4.2	Calibration result for SM area during May 2, 2010 for Point 2	81
Figure 4.3	Calibration result for SM area during May 2, 2010 for Point 3	83
Figure 4.4	Model calibration (Runoff event on February 26, 2009)	89
Figure 4.5	Model verification (Runoff event on December 26, 2008)	89
Figure 4.6	Comparison of normal and simulated water level	91
Figure 4.7	Flood depth and surcharge state for the node and link respectively	92
Figure 4.8	Cross-section of trunk drain showing the water flowpath due to backwater effect	93
Figure 4.9	Cross-section of earth drain showing the water flowpath due to backwater effect	93
Figure 4.10	Drainage flow and velocity at trunk drain in SM residential area	95
Figure 4.11	Drainage flow and velocity at earth drain in SM residential area	95

Figure 4.12	Comparison flood depth between internal flood and external flood	98
Figure 4.13	Cross-section of trunk drain during internal flood	99
Figure 4.14	Cross-section of earth drain during internal flood	99
Figure 4.15	Observation point of flow, velocity and average flood depth with internal and external flood	100
Figure 4.16	Comparison of flow for internal and external flood for trunk drain during December 26, 2008 flood	103
Figure 4.17	Comparison of velocity for internal and external flood for trunk drain during December 26, 2008 flood	103
Figure 4.18	Comparison of flow for internal and external flood for earth drain during December 26, 2008 flood	104
Figure 4.19	Comparison of velocity for internal and external flood for earth drain during December 26, 2008 flood	104
Figure 4.20	Flood condition of existing SM residential drainage system with and without levee	107
Figure 4.21	Cross-section of trunk drain with levee protection	109
Figure 4.22	Cross-section of earth drain with levee protection	109
Figure 4.23	Flap gate for Outlet 1	110
Figure 4.24	Flap gate for Outlet 2	110
Figure 4.25	Flap gate for Outlet 3	111
Figure 4.26	Comparison on flow graph at the trunk with and without levee	111
Figure 4.27	Comparison on flow graph at the earth drain with and without levee	112

Figure 4.28	Comparison of water depth of different design rainfall for 2, 5, 10 and 20 years ARI	115
Figure 4.29	Flood condition with levee and after 20 years ARI	117

# **CHAPTER 1**

## **INTRODUCTION**

### **1.1 Introduction**

Water is a crucial element to all of us. Human health and socio-economic welfares are dependent on the adequate supplies of suitable quality water. Conversely, excessiveness of water will result in socio-economic damages and loss of lives due to floods. Climate changes, urbanization, increasing utilization of flood plains and reduction in the natural retention capacity of catchment play a vital role in contribution to flood.

In this study, flood prevention and mitigation involve both hydrology and hydraulics study on the urban drainage system. Drainage system depends on the amount of runoff expected during a high intensity rainfall in a short period of time, tidal influences and the elevation of the area being drained. The resulting stormwater which cannot be drained quickly and coincided with the King Tide, leads to water



accumulation and flooding in streets, roads and residential areas. As a result, drainage system in Sibul is the most important infrastructure to protect homes, businesses, roads and agricultural lands from frequent periods of “excess” water whether from rain or tidal. Many Sibul’s soils, too, are poorly drained in which its soil type is mainly soft peat. Additionally, Sibul is on a low-lying deltaic area that distress most of the town and suburb areas with water whenever there is rain or tidal.

Understanding the link between drainage systems and our environment is important for a full understanding of this issue. With the rapid development of Sibul Town, effect on land use has paralyzed the drainage system. Direct runoff from storm water towards the drain has increased the volume and velocity of the water flow that overflows into the town and causes flood.

Apart from that, siltation is also a major crisis that contributes to ineffective drainage system in Sibul. Sedimentation of soil in the river mouth of Seduan River (Figure 1.1) has constricted water flow from upstream. As time flies, the erosion process, sedimentation and changing shape of the riverbank have changed the depth of the river in the area. When King Tide struck, the tidal water will back-filled the drainage system of the residential houses along the riverbank that causes inundation to the areas.




Figure 1.1: Existing of sandbar (circled on right photo) at the mouth of Seduan River (see arrow). A Google photo taken in 2001 (left) and photo taken in 2008 (right).

Briefly, improvement on floodplain management should be implemented in the Sibul Town to remove excess water from poorly drained areas and provide trafficable condition for flood mitigation purposes. The Federal Government had injected RM 300 million for the flood mitigation project for phase I and might extend beyond the 10<sup>th</sup> and 11<sup>th</sup> Malaysia Plans which cost more than RM1 billion when completed (Eastern Times, 2010).